

Alto 260

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Length (inches)** 12.6
- **Thickness (inches)** 0.031 (31 mil)
- **Wrist** Straight cuff
- **Colour/Color** Black
- **Interior finish** Flocked
- **Exterior finish** Embossed texture, chlorinated
- **Size / EAN** 7 8 9 10 11
- **Packaging** 1 pair/bag - 10 pairs/bag - 50 pairs/carton



PERFORMANCE RESULTS

Certification category 3

CE 0334



Dexterity EN 420 : 5/5



2120X

Legends

EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS

0-4 0-5 0-4 0-4 A-F (P)

- Impact protection
- Cut resistance according to ISO 13997
- Puncture resistance
- Tear resistance
- Blade cut resistance
- Abrasion resistance

EN 407 THERMAL RISKS heat and fire



PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4

- Resistance to large quantities of molten metal
- Resistance to small drops of molten metal
- Radiant heat resistant
- Convective heat resistance
- Contact heat resistance
- Burning behaviour

CHEMICAL RISKS

EN ISO 374-1



Type A
U V W X Y Z

A Methanol
B Acetone
C Acetonitrile
D Dichloromethane
E Carbon Disulfide
F Toluene
G Diethylamine
H Tetrahydrofuran
I Ethyl acetate

EN ISO 374-1



Type B
X Y Z

J n-Heptane
K Sodium hydroxide 40%
L Sulphuric acid 96%
M Nitric acid 65%
N Acetic acid 99%
O Ammonia 25%
P Hydrogen peroxide 30%
S Hydrofluoric acid 40%
T Formaldehyde 37%

EN ISO 374-1



Type C

MICRO-ORGANISMS

EN ISO 374-5



Protection against bacteria, fungi

EN ISO 374-5



Protection against bacteria, fungi, virus

VIRUS



COLD HAZARDS

PERFORMANCE LEVELS

0-4 0-4 0 or 1

- Water permeability
- Contact cold resistance
- Convective cold resistance



RADIOACTIVE CONTAMINATION



CUT RESISTANCE

A1 ≥ 200 G	A4 ≥ 1500 G	A7 ≥ 4000 G
A2 ≥ 500 G	A5 ≥ 2200 G	A8 ≥ 5000 G
A3 ≥ 1000 G	A6 ≥ 3000 G	A9 ≥ 6000 G

For more details: www.mapa-pro.com

MAPA
PROFESSIONAL

www.mapa-pro.com

SPECIFIC ADVANTAGES

- Good protection against chemical products
- Flock-lining adds comfort and perspiration absorption
- Embossed textured grip ensures good handling of slippery objects
- Previous name : Alto Plus 260

MAIN FIELDS OF USE

Other industries

- Maintenance in wet environments

Aeronautics industry

- Work with composite materials (resins)

Chemical industry

- Resin-working
- Resin and adhesive manufacturing
- Common handling Tasks

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- • It is not recommended for persons sensitized to natural latex, dithiocarbamates and thiazoles to use these gloves.
- • Put the gloves on dry, clean hands.
- • Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the MAPA Technical Customer Service to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

- Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

Laundering conditions

- Before taking off the gloves, clean them as appropriate
- • in use with a solvent : rub over with a dry cloth
- • in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth
- • Caution : using the gloves or submitting them to another cleaning or laundering process can alter their performance levels.

Drying conditions

- Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

- This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/08/18/1672
- **Issued by the notified body nr** : 0075 - C.T.C. 4 rue Herman Frenkel-69367 LYON cedex 07-France
- **Quality assurance certificat** : 0334 Asqual 14 rue des Reculettes - 75013 Paris -France